

1. Description


1.1. Project

Project Name	STM32F0_SSD1306
Board Name	STM32F0DISCOVERY
Generated with:	STM32CubeMX 5.6.0
Date	11/01/2023

1.2. MCU

MCU Series	STM32F0
MCU Line	STM32F0x1
MCU name	STM32F051R8Tx
MCU Package	LQFP64
MCU Pin number	64

2. Pinout Configuration




3. Pins Configuration

Pin Number LQFP64	Pin Name (function after reset)	Pin Type	Alternate Function(s)	Label
1	VBAT	Power		
7	NRST	Reset		
12	VSSA	Power		
13	VDDA	Power		
14	PA0	I/O	GPIO_EXTI0	B1 [Blue PushButton]
31	VSS	Power		
32	VDD	Power		
39	PC8 *	I/O	GPIO_Output	LD4 [Blue Led]
40	PC9 *	I/O	GPIO_Output	LD3 [Green Led]
46	PA13	I/O	SYS_SWDIO	SWDIO
49	PA14	I/O	SYS_SWCLK	SWCLK
58	PB6	I/O	I2C1_SCL	
59	PB7	I/O	I2C1_SDA	
60	BOOT0	Boot		
63	VSS	Power		
64	VDD	Power		

* The pin is affected with an I/O function

4. Clock Tree Configuration



5. Software Project

5.1. Project Settings

Name	Value
Project Name	STM32F0_SSD1306
Project Folder	D:\Dokumenty\PROJEKTY\STM32_SSD1306_OLED\STM32F0_SSD1306
Toolchain / IDE	Makefile
Firmware Package Name and Version	STM32Cube FW_F0 V1.11.3

5.2. Code Generation Settings

Name	Value
STM32Cube MCU packages and embedded software	Copy only the necessary library files
Generate peripheral initialization as a pair of '.c/.h' files	Yes
Backup previously generated files when re-generating	No
Delete previously generated files when not re-generated	Yes
Set all free pins as analog (to optimize the power consumption)	No

6. Power Consumption Calculator report

6.1. Microcontroller Selection

Series	STM32F0
Line	STM32F0x1
MCU	STM32F051R8Tx
Datasheet	022265_Rev7

6.2. Parameter Selection

Temperature	25
Vdd	3.3

6.3. Battery Selection

Battery	Li-SOCL2(A3400)
Capacity	3400.0 mAh
Self Discharge	0.08 %/month
Nominal Voltage	3.6 V
Max Cont Current	100.0 mA
Max Pulse Current	200.0 mA
Cells in series	1
Cells in parallel	1


6.4. Sequence

Step	Step1	Step2
Mode	RUN	STOP
Vdd	3.3	3.3
Voltage Source	Battery	Battery
Range	No Scale	No Scale
Fetch Type	FLASH	n/a
CPU Frequency	48 MHz	0 Hz
Clock Configuration	HSE PLL	Regulator LP
Clock Source Frequency	8 MHz	0 Hz
Peripherals		
Additional Cons.	0 mA	0 mA
Average Current	13.45 mA	6.2 µA
Duration	0.1 ms	0.9 ms
DMIPS	0.0	0.0
T_a Max	103	105
Category	In DS Table	In DS Table

6.5. RESULTS

Sequence Time	1 ms	Average Current	1.35 mA
Battery Life	3 months, 13 days, 8 hours	Average DMIPS	0.0 DMIPS

6.6. Chart



7. IPs and Middleware Configuration

7.1. GPIO

7.2. I2C1

I2C: I2C

7.2.1. Parameter Settings:

Timing configuration:

I2C Speed Mode	Standard Mode
I2C Speed Frequency (KHz)	100
Rise Time (ns)	0
Fall Time (ns)	0
Coefficient of Digital Filter	0
Analog Filter	Enabled
Timing	0x2000090E

Slave Features:

Clock No Stretch Mode	Disabled
General Call Address Detection	Disabled
Primary Address Length selection	7-bit
Dual Address Acknowledged	Disabled
Primary slave address	0

7.3. RCC

7.3.1. Parameter Settings:

System Parameters:

VDD voltage (V)	3.3
Prefetch Buffer	Enabled
Flash Latency(WS)	1 WS (2 CPU cycle)

RCC Parameters:

HSI Calibration Value	16
HSE Startup Timeout Value (ms)	100
LSE Startup Timeout Value (ms)	5000

7.4. SYS

mode: Debug Serial Wire

Timebase Source: SysTick

* User modified value

8. System Configuration

8.1. GPIO configuration

IP	Pin	Signal	GPIO mode	GPIO pull/up pull down	Max Speed	User Label
I2C1	PB6	I2C1_SCL	Alternate Function Open Drain	Pull-up	High *	
	PB7	I2C1_SDA	Alternate Function Open Drain	Pull-up	High *	
SYS	PA13	SYS_SWDIO	n/a	n/a	n/a	SWDIO
	PA14	SYS_SWCLK	n/a	n/a	n/a	SWCLK
GPIO	PA0	GPIO_EXTI0	External Event Mode with Rising edge trigger detection *	No pull-up and no pull-down	n/a	B1 [Blue PushButton]
	PC8	GPIO_Output	Output Push Pull	No pull-up and no pull-down	Low	LD4 [Blue Led]
	PC9	GPIO_Output	Output Push Pull	No pull-up and no pull-down	Low	LD3 [Green Led]

8.2. DMA configuration

nothing configured in DMA service

8.3. NVIC configuration

Interrupt Table	Enable	Preenmption Priority	SubPriority
Non maskable interrupt	true	0	0
Hard fault interrupt	true	0	0
System service call via SWI instruction	true	0	0
Pendable request for system service	true	0	0
System tick timer	true	0	0
PVD interrupt through EXTI Line16		unused	
Flash global interrupt		unused	
RCC global interrupt		unused	
I2C1 event global interrupt / I2C1 wake-up interrupt through EXTI line 23		unused	

* User modified value

9. Predefined Views - Category view : Current

Middleware

System Core

Analog

Timers

Connectivity

Multimedia

Computing

DMA

I2C1

GPIO



NVIC

RCC

SYS

10. Software Pack Report